

# Mitel MiVoice 5540 IP Console

Affordability and simplicity in an attendant console

## Key Features

- Highly-visible backlit tilt display
- 14 fixed function keys
- Convenient teleworker functionality
- Hospitality features including room status, guest telephony privileges and automatic wake-up calls
- Two integrated headset / handset jacks



The Mitel® MiVoice 5540 IP Console is the ideal attendant solution for small and medium businesses using the MiVoice Business (formerly Mitel Communications Director) solution or the Mitel SX-200 IP Communications Platform (ICP). This economical answering point supports the same tried and tested functionality of its predecessor – the Mitel SuperConsole® 1000 Attendant Console – with the additional benefits of an IP platform base. It can be used as an attendant console, a sub-attendant position for departments or workgroups, or as a back-up answering position.

Affordability, simplicity, and a broad range of standard and specialty functions make the MiVoice 5540 IP Console the practical choice for small and medium business customers.

## Ideal Hospitality Solution

Hospitality customers will find that the MiVoice 5540 IP Console is the perfect attendant solution for their unique hotel / motel requirements. Using the highly integrated hotel / motel feature package on both the SX-200 ICP and the MiVoice Business communications platforms, hotel operators can accurately enter room data, easily update guest status, and gain greater flexibility and control of incoming, outgoing, and room-to-room calls.

Hospitality-specific features allow attendants to program automatic or personal wake-up calls, request reports of all current wake-up calls, receive room status updates, activate direct inward dialing so that outside callers can reach guests without front desk assistance, and much more. The MiVoice 5540 IP Console combines ease of use

with extended specialty functions to create an economical attendant solution that will suit the needs of any hospitality enterprise.

## MiVoice 5540 IP Console Features

- *Highly visible, four-line, 80-character, backlit, tilt display shows date, time, call status information, calling line identification, and calls waiting*
- *14 fixed function keys dedicated to basic and enhanced call-handling activities*
- *10 softkeys that control access to the attendant features through call state sensitive keys*
- *Support for the MiVoice Border Gateway and Mitel Teleworker Solution allowing the console to be connected remotely, providing attendants with the ability to work anywhere, and anytime*
- *Multiple call hold positions and line appearances*

- *Mitel Intelligent Directory and Mitel Live Content Suite applications support*
- *Support for Mitel Teleworker Solution, Automatic Call Distribution (ACD) agent and supervisor, hot desking, and resiliency*
- *Direct connection of 48-button Mitel IP Programmable Key Module 48 (PKM), providing up to 96 additional Direct Station Select (DSS) / Busy Lamp Field (BLF) keys (SX-200 ICP only)*
- *Third-party cordless headset integrated functions include: Call Answer, Call Cancel, Audio Controls, and training mode support*
- *Access to integrated Mitel Hospitality features including room status, guest telephony privileges, automatic wake-up calls, room to room call blocking, occupancy status, guest check-in / check-out, guest reports, and many more hotel / motel functions*
- *Hands-free speakerphone operation (full duplex)*
- *Supports multiple languages for global customers: English, French, Spanish, German, Italian, Dutch, Portuguese, Simplified Chinese*
- *Resiliency support with the MiVoice Business solution (only)*
- *Secure Call Recorder Connector (SCRC) support as well as standard Record-a-Call functionality (MiVoice Business only)*
- *Two integrated headset / handset jacks*
- *Dual-port IP console (10/100 MB switched Ethernet) – connect a computer and a console with a single Ethernet drop*
- *Multiple powering options (IEEE 802.3af compliant)*
- *Power conservation design: reduces power consumption for overall energy savings*

## Additional Advanced Attendant Functions

In addition to basic call handling, the attendant is empowered to:

- *Speak to multiple parties through conference calling*
- *Speak with parties in the conference individually through call splitting*
- *Page external paging equipment with overhead paging*
- *Page individual extension numbers using their telephone speaker with extension paging*
- *Change / clear users' status to "Do Not Disturb"*
- *Set / clear "Call Forward Always" on an extension*
- *Clear Call Forward Always, Do Not Disturb, and Message Waiting indications across all*
- *View system alarms and emergency call alarms*

## Dual Port

Two 10/100 MB switched Ethernet ports

## Powering Options

The MiVoice 5540 IP Console accepts standards-based (IEEE 802.3af) power over the LAN via spare pair or signal pair, and supports 48 V DC Ethernet / AC Power wall adapter. It can be powered via a powered switch, a mid-span power hub, or by local 48 V Ethernet power.

## Power Adapter (Optional)

Input: 100 V 50 – 60 Hz or 240V 50 Hz

Output: 48 V DC LAN

## POWER CONSUMPTION

Specification	WATTAGE
Idle	4.96 W
Typical	6.06 W
Max	7.27 W

## ENVIRONMENTAL CONDITIONS

Specification	TEMPERATURE	HUMIDITY
Operational	+4°C to +49°C	34% at +49°C 95% at +29°C
Storage	-40°C to +66°C	15% at +66°C 95% at +29°C

## REGULATORY APPROVALS

EMC	Safety	TELECOM
<ul style="list-style-type: none"> <li>» CANADA: ICES-003 (CLASS B)</li> <li>» USA: CFR TITLE 47, PART 15 (CLASS B)</li> <li>» EU: EN55024 (EU), EN55022 (CLASS B)</li> <li>» AUSTRALIA / NEW ZEALAND : AS/NZS CISPR 22</li> </ul>	<ul style="list-style-type: none"> <li>» CANADA: CSA C22.2 NO. 60950-1</li> <li>» USA: UL 60950-1</li> <li>» EU: EN 60950, EN 60950-1</li> <li>» AUSTRALIA / NEW ZEALAND: AS/NZS 60950-1</li> </ul>	<ul style="list-style-type: none"> <li>» CANADA: CS03 Part V (hearing aid compatible)</li> <li>» USA: FCC Part 68 (CFR 47) (hearing aid compatible)</li> <li>» AUSTRALIA / NEW ZEALAND: PTC220, AS/ACIS, S004</li> </ul>

## MiVOICE 5540 IP CONSOLE SPECIFICATIONS

Voice Traffic & Signaling	Voice QoS	Size (L x W x H)	Weight	MTBF	CODEC / Compression
» RTP over UDP / MiNet over TCP	» IEEE 802.1p/q	» 9.1" x 7.5" x 3.5" (23cm x 19cm x 9cm)	» 4.37 lbs (1.98 kgs)	» 20.7 years	» G.711, G.729a

## System Requirements

- *MiVoice Business – Release 4.0 (SP1) or higher (formerly Mitel Communications Director)*
- *Mitel SX-200 IP Communications Platform (ICP) – Release 5.0 or higher*